

Cable Spools

22 AWG & 18 AWG PVC

Cable Spools



Specifications

Cable	Oil-resistant PVC jacket, PVC insulated conductors, 300V
Cable Rating	UL AWM style 2661 VW-1 105C 300V, CSA AWM A/B I/II 80C 300V FT1, UV oil and water resistant
Operating Temperature—C (F)	-20...+105° (-4...+221°)

Features

- 3-, 4-, 5- and 6-conductor AWM styles
- Braided shielded or unshielded versions
- Yellow, blue, or black PVC cable jacket
- 22 AWG or 18 AWG conductors
- IEC or Automotive color-coded conductors

Product Selection

Jacket Material	Number of Conductors	Color Code	Jacket Color	Wire Gauge	Nominal O.D.—mm (in)	Shielding	Cat. No.
PVC	2	Brown, Blue	Yellow	22 AWG	5.3 (0.21)	None	889-C2AC-S**
	3	Brown, Blue, Black	Yellow	22 AWG	5.3 (0.21)	None	889-C3AC-S**
		Green, Red w/Black stripe, Red w/White stripe	Yellow	22 AWG	6.7 (0.26)	Braided	889-C3ECA-S**
			Yellow	18 AWG	6.7 (0.26)	None	889-C3AEA-S**
		4	Brown, White, Blue, Black	Yellow	22 AWG	5.3 (0.21)	None
	Black			22 AWG	5.3 (0.21)	None	889-C4BC-S**
	Blue			22 AWG	5.3 (0.21)	None	889-C4LC-S**
	Yellow			22 AWG	6.7 (0.26)	Braided	889-C4EC-S**
	Yellow			18 AWG	6.7 (0.26)	None	889-C4AE-S**
	Yellow			22 AWG	5.5 (0.22)	Foil	889-C4FC-S**
	Green, Red w/Black stripe, Red w/White stripe, Red		Yellow	22 AWG	6.7 (0.26)	Braided	889-C4ECA-S**
			Yellow	18 AWG	6.7 (0.26)	None	889-C4AEA-S**
	5	Brown, White, Blue, Black, Grey	Yellow	22 AWG	6.0 (0.24)	None	889-C5AC-S**
			Black	22 AWG	6.0 (0.24)	None	889-C5BC-S**
			Yellow	22 AWG	6.7 (0.26)	Braided	889-C5EC-S**
		Green, Red w/Black stripe, Red w/White stripe, Red, Red w/Yellow stripe	Yellow	22 AWG	6.7 (0.26)	None	889-C5ECA-S**
			Yellow	18 AWG	6.7 (0.26)	None	889-C5AEA-S**
	6	Green, Red w/Black, Red w/White, Red, Red w/Yellow, Red w/Blue stripe	Yellow	22 AWG	6.7 (0.26)	Braided	889-C6ECA-S**

* Replace symbol with 50 (50 m), 100 (100 m) or 200 (200 m) for standard cable lengths.